

# TITANLENE® LDF 260GG

Low Density Polyethylene

Lotte Chemical Titan (M) Sdn. Bhd.



ides.com/prospector

## Technical Data

### Product Description

LDF260GG is a low density polyethylene resin for film extrusion. LDF260GG has medium slip and anti-block additives. LDF260GG meets the U.S. Food and Drug Administration (FDA) criteria for food contact use as specified in 21 CFR 177.1520 (c) 2.1 & (c) 2.2.

#### APPLICATIONS:

Laundry film, Textile packaging, Produce film, Diaper backing.

#### Characteristics:

Good drawdown and excellent processability.

### General

Material Status	• Commercial: Active		
Literature <sup>1</sup>	• <a href="#">Technical Datasheet (English)</a>		
Search for UL Yellow Card	• <a href="#">Lotte Chemical Titan (M) Sdn. Bhd.</a>		
Availability	• Asia Pacific		
Additive	• Antiblock	• Slip	
Features	• Antiblocking	• Good Processability	• Medium Slip
	• Good Drawdown	• Low Density	
Uses	• Film	• Packaging	
Agency Ratings	• FDA 21 CFR 177.1520(c) 2.1	• FDA 21 CFR 177.1520(c) 2.2	
Processing Method	• Film Extrusion		

Physical	Nominal Value Unit	Test Method
Density	0.922 g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	5.0 g/10 min	ASTM D1238

Films	Nominal Value Unit	Test Method
Film Thickness - Tested	30 µm	
Secant Modulus		ASTM D882
1% Secant, MD : 30 µm, Blown Film	186 MPa	
1% Secant, TD : 30 µm, Blown Film	206 MPa	
Tensile Strength		ASTM D882
MD : Break, 30 µm, Blown Film	19.6 MPa	
TD : Break, 30 µm, Blown Film	17.7 MPa	
Tensile Elongation		ASTM D882
MD : Break, 30 µm, Blown Film	250 %	
TD : Break, 30 µm, Blown Film	440 %	
Dart Drop Impact (30 µm, Blown Film)	75 g	ASTM D1709
Elmendorf Tear Strength		ASTM D1922
MD : 30 µm, Blown Film	290 g	
TD : 30 µm, Blown Film	120 g	

Thermal	Nominal Value Unit	Test Method
Vicat Softening Temperature	93.0 °C	ASTM D1525

Optical	Nominal Value Unit	Test Method
Haze (30.0 µm, Blown Film)	7.0 %	ASTM D1003

Extrusion	Nominal Value Unit
Melt Temperature	160 to 180 °C

### Notes

<sup>1</sup> These links provide you with access to supplier literature. We work hard to keep them up to date; however you may find the most current literature from the supplier.

<sup>2</sup> Typical properties: these are not to be construed as specifications.

## TITANLENE® LDF 260GG

Low Density Polyethylene

**Lotte Chemical Titan (M) Sdn. Bhd.**

### Where to Buy

#### Supplier

**Lotte Chemical Titan (M) Sdn. Bhd.**

Kuala Lumpur, Malaysia

**Telephone:** +603-2093 4222

**Web:** <http://www.titangroup.com/>


#### Distributor

Please contact the supplier to find a distributor for TITANLENE® LDF 260GG

randomplastic



Founded in 1986 and based in Laramie, Wyoming, IDES is now part of the UL family of companies. UL is a premier global independent safety science company with more than a century of proven history. Employing nearly 10,000 professionals in over 100 countries, UL has five distinct business units -- Product Safety, Environment, Life & Health, Knowledge Services and Verification Services -- to meet the expanding needs of our customers and to deliver on our public safety mission.



### Prospector Plastics Database - [www.ides.com/prospector](http://www.ides.com/prospector)

Prospector is a searchable online database that includes 85,000 data sheets from 875 manufacturers and 44,000 UL yellow cards. Each data sheet includes property, processing and supplier contact information. Prospector is relied on by nearly 400,000 design engineers and plastics processors. Using Prospector, they save time with plastic material selection by quickly and easily referencing technical information critical to the success of their products.

*"Prospector is absolutely the best and most well-known search engine for plastic raw materials in the world. We use Prospector every day – it's a real time saver!"*

– Birgit Elvardt Bader, Production Manager, Micotron

#### Power Searches

**Property Search** – select plastics by 500 key properties and design parameters.

**Alternative Resins Search** – find replacement plastics within minutes.

**Automotive Plastics Search** – easily locate automotive approved plastics.

**Curve Data** – view, overlay and export curve data.



### Material Data Management – [www.ides.com/datasheets](http://www.ides.com/datasheets)

With our data management services, plastic suppliers and distributors can have custom search interfaces available on their website for their customers, website visitors, sales and customer service teams. These provide intuitive ways to find and view technical data sheets for their products.

*"With UL IDES data services, our website now displays the most current information on the products we distribute and links to our backend RFQ and sales order system, adding both value and service for our customers."*

– Kevin Chase, Owner & President, Chase Plastics



### Advertising – [www.ides.com/advertise](http://www.ides.com/advertise)

Reach 365,000 pre-qualified plastics professionals and generate leads with proven techniques. Electronic newsletter insertions, sponsored webinars and powerful online ads are available to make the most of your lead-generation program.

For more information, call: 800.788.4668 or 307.742.9227 ext. 220