

BU7100

High-density polyethylene (HDPE)



Description

BU7100 is a high-density polyethylene resin produced by Univation(Gas) Process, suitable for Blow molding which has excellent ESCR and stiffness / impact strength

Characteristics

- High Melt-Strength
- Excellent Formability
- Excellent ESCR

Applications

- Large size industrial containers and drum, jerry can, Large part for blow (buoy, median strip)

Properties

	Properties	Test Method		Values	Nominal
Physical	Melt Flow Index (190°C, 21.6kg)	ASTM	D1238	10.0	g/10min
	Density	ASTM	D1505	0.948	g/cm ³
Mechanical	Tensile Stress (Yield)	ASTM	D638	260	kgf/cm ²
	Tensile Strain (Break)	ASTM	D638	> 600	%
	Flexural Modulus	ASTM	D790	11,200	kgf/cm ²
	Notched IZOD Impact Strength (23°C)	ASTM	D256	NB	kgf-cm/cm
	ESCR	ASTM	D1693	> 1,000	F50hr

• NOTE : these are not to be construed as specifications

*DISCLAIMER : THIS DOCUMENT (INCLUDING ANY ENCLOSURES AND ATTACHEMENTS) HAS BEEN PREPARED FOR THE EXCLUSIVE USE AND BENEFIT OF THE ADDRESSEE(S) AND SOLELY FOR THE PURPOSE FOR WHICH IT IS PROVIDED. LOTTE CHEMICAL MAKES NO WARRANTY OR REPRESENTATION WHATSOEVER, EXPRESS OR IMPLIED, AS TO THE ACCURACY, COMPLETENESS, MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE WITH RESPECT TO THIS DOCUMENT OR ANY INFORMATION HEREIN; AND LOTTE CHEMICAL ASSUMES NO LIABILITY WHATSOEVER WITHOUT LIMITATION WITH RESPECT TO ANY DAMAGES INCLUDING, BUT NOT LIMITED TO, DIRECT, INDIRECT, SPECIAL, CONSEQUENTIAL, OR PUNITIVE DAMAGES ARISING OUT OF, RESULTING FROM, OR ANY WAY CONNECTED TO ANY USE OF THIS DOCUMENT OR ANY INFORMATION HEREIN.

